

Checking Points for Accidental Damage on XKE Body and Front Frame Section

A.	Upper hole of top mounting flange to lower hole		N.	Outer face of front sub frame tube to center
	of lower mounting flange on front sub frame.	103/4"		line of car.
В.	Center line front hub to rear mounting flange		O.	Center line of radiator mounting hole to cen
	front sub frame.	145/32"		line of car.
C.	Second from top hole on engine mounting post		P.	Center line of front frame tube to center line
	to datum line.	101/8"		of radiator mounting hole.
D.	Lower rear face of front crossmember to front		Q	Top outer hole of front sub frame upper mou
	bulkhead face.	3525/32"		flange to center line of car.
E.	Upper rear face of front crossmember to front		R.	Inner hole of outer side member mounting fla
	bulkhead face.	353/4"		to center line of car.
F.	Centerline of holes on engine mounting post to		S.	Inner hole of top side member mounting flan
	front bulkhead.	$25^{1/8}$ "		to center line of car.
G.	Top hole in outer side member to datum line.	31/8"	T.	Rear mounting flange face of outer side mem
H.	Top hole in upper outrigger flange to datum line.			to front bulkhead face.
$15^{1}$			U.	Center line of hole in front of body underfran
I.	Center of radius arm mounting post to front			side of member to center line of car.
	face of rear wheel aperture.	215/16"	V.	Outer hole of outrigger mounting bracket to
J.	Center line of front lower mounting hole to front			center line of car.
	face of rear wheel aperture.	923/32"	W.	Center line of radius arm mounting post to
K.	Center line of front lower mounting hole to center	,		center line of car.
	line of rear mounting hole.	1037/64"	X.	Center line of hole in rear of body underfram
L.	Center line of lower mounting hole to datum line.	87/64"		member to center line of car.
M.	Center line of rear lower mounting hole to rear		Y.	Outside face of rear suspension mounting po
	number plate panel.	3143/64"		to center line of car.

	mic of car.				
O.	Center line of radiator mounting hole to center				
	line of car. 81/4	"			
P.	Center line of front frame tube to center line				
	of radiator mounting hole. 53/4	"			
Q	Top outer hole of front sub frame upper mounting				
	flange to center line of car. $10^{11/16}$	"			
R.	Inner hole of outer side member mounting flange				
	to center line of car. 227/8	"			
S.	Inner hole of top side member mounting flange				
	to center line of car. 85/8	"			
T.	Rear mounting flange face of outer side member				
	to front bulkhead face.	"			
U.	Center line of hole in front of body underframe				
	side of member to center line of car. 925/32	"			
V.	Outer hole of outrigger mounting bracket to				
	center line of car. 26 <sup>5/8</sup>	"			
W.	Center line of radius arm mounting post to				
	center line of car. 18	"			
X.	Center line of hole in rear of body underframe side				
	member to center line of car. 91/8	"			
Y.	Outside face of rear suspension mounting points				
	to center line of car. 99/16	"			

 $16^{15/16}$ "